

Direct view series



DESCRIPTION & FEATURES

The DirectView DV-164 is a small, lowcost operator interface. It can be directly connected to our PLC's. The DV-164 does not require any configuration software. Instead, setup is performed through special reserved memory locations inside of our PLC. These special memory areas tell the DV-164 which modes to use, and more importantly, where to get its display data.

View memory status: Display up to four variable address values at a time on a single screen. View bit status: Display 32 bits (4 lines of 8 bits) or
64 bits (4 lines of 16 bits) at a time on a single screen. Bit data types can include I/O points, control relays, timer/ counter and stage bits.

Change values of memory locations: Up to 16 different variable memory values can be changed (32 for DL405). Just move the cursor over the appropriate digit and press the increment (+)/decrement (-) keys.

Units per PLC/CPU: Only one DV-164.

HEMKUNT electronics specializes in customizing designs to specific customer needs for a wide range of applications. Please feel free contact us to provide the optimal solution for your specific needs.

FEATURES

LOW COST.

From simple pushbutton/indicator panel to four-line by 16-character LCD display

Supports all Direct micro controllers and micro processors.

TECHNICAL DATA

Max. Distance : 15 feet from the CPU

Connector : RS 232

Power Consumption : 150mA @ 5VDC max

(supplied by PLC communication port)

Agency Approval : CE , ROHS

 Storage Temp
 :
 -4 to 158°F (-20 to 70°C)

 Operating Temp
 :
 32 to 122°F (0 to 50°C)

 Humidity
 :
 5-95% (non-condensing)

 Vibration Resistance
 :
 MIL STD 810C Method 514.2

 Shock Resistance
 :
 MIL STD 810C Method 516.2

Atmosphere : No corrosive gases

As a result of our policy of continual improvement, the information in this document is subject to change without any notice and it is intended only as general guidance on product performance and suitability. This information shall not form part of any contract.

our product should be installed by a qualified personnel only, therefore any use of this application is at the installer's own risk and should be accessed appropriately.

HEMKUNT ELECTRONICS

Contact Details: Website- www.hemkuntelectronics.com

EMail- hemkuntalert@gmail.com

Address- 4583/13 Jai Mata Market, Tri Nagar, Delhi- 110035

Telephone numbers- 011-27394466,+91-9810822092, +91-8800445952